

SHOCK MISER™ SPECIFICATION SHEET		
GT-140 MOD Box x AX39 Pin		
Shock Miser™ Body Specs		
OD:	5.25	in
ID:	VARIABLE	in
Weight (Sub Only):	130	lbs max
Assembly Weight	150	lbs max
Max Flow Rate	450	GPM
Grade:	4145 HT	
Length (Makeup):	3.5	ft
Uphole Connection Specs		
Connection:	GT-140 MOD Box	
Box OD:	5.25	in
Connection ID:	3.63	in
SMYS:	125,000	psi (min)
Recommended MUT	20,000	ft-lbs
Connection Tensile:	694,859	lbs
Connection Torsional:	30,911	ft-lbs
Downhole Connection Specs		
Connection:	AX39 PIN	(XTF-39 AVAILABLE)
Body OD:	5.25	in
Connection ID:	2.38	in
SMYS:	125,000	psi (min)
Recommended MUT	20,000	ft-lbs
Connection Tensile:	693,399	lbs
Connection Torsional:	40,831	ft-lbs

SHOCK MISER™ SPECIFICATION SHEET		
GT-140 MOD Box x DS-42 Pin		
Shock Miser™ Body Specs		
OD:	5.25	in
ID:	VARIABLE	in
Weight (Sub Only):	130	lbs max
Assembly Weight	150	lbs max
Max Flow Rate	450	GPM
Grade:	4145 HT	
Length (Makeup):	3.5	ft
Uphole Connection Specs		
Connection:	GT-140 MOD Box	
Box OD:	5.25	in
Connection ID:	3.63	in
SMYS:	125,000	psi (min)
Recommended MUT	20,000	ft-lbs
Connection Tensile:	694,859	lbs
Connection Torsional:	30,911	ft-lbs
Downhole Connection Specs		
Connection:	DS-42	
Body OD:	5.25	in
Connection ID:	2.38	in
SMYS:	125,000	psi (min)
Recommended MUT	20,000	ft-lbs
Connection Tensile:	557,523	lbs
Connection Torsional:	33,783	ft-lbs

SHOCK MISER™ SPECIFICATION SHEET		
GT-139 MOD Box x AX-39 Pin		
Shock Miser™ Body Specs		
OD:	5.0	in
ID:	VARIABLE	in
Weight (Sub Only):	120	lbs max
Assembly Weight	135	lbs max
Max Flow Rate	350	GPM
Grade:	4145 HT	
Length (Makeup):	3.5	ft
Uphole Connection Specs		
Connection:	GT-139 MOD Box	
Box OD:	5.00	in
Connection ID:	3.44	in
SMYS:	125,000	psi (min)
Recommended MUT	15,000	ft-lbs
Connection Tensile:	619,695	lbs
Connection Torsional:	25,912	ft-lbs
Downhole Connection Specs		
Connection:	AX39 PIN	(XTF-39 AVAILABLE)
Body OD:	5.00	in
Connection ID:	2.38	in
SMYS:	125,000	psi (min)
Recommended MUT	20,000	ft-lbs
Connection Tensile:	693,399	lbs
Connection Torsional:	40,831	ft-lbs